

Document Detail

Type: 0060-PR DT

Document No.: 0060-Com-Fit Mask Specification Summary[1]

Title: Com-Fit Face Mask Specification Summary Memo

Status: CURRENT

Effective Date: 27-Apr-2020

<u>Review</u>

Owner Role	Actor	Sign-off Date	Sign-off By
DPD Document Change Order Initiator	Maeve Bowers	27-Apr-2020 3:53 pm (GMT)	DIVVP745
DPD Clinical	Michele Lash	27-Apr-2020 6:49 pm (GMT)	DITOC098
DPD Document Control	Leslie Lentz	27-Apr-2020 7:37 pm (GMT)	PCLJL684

MEMORANDUM



Table 1 below summarizes the performance requirements met for the Com-Fit product line of face masks.

Table 1 Com-Fit Mask Classifications, ASTM F2100 and EN 14683					
P/N	N Product Description		EN 14683 Type		
20324	Com-Fit Fluid Resistant Procedural Blue Face Mask with Soft Earloop	-	IIR		
20325	Com-Fit Fluid Resistant Procedural Pink Face Mask with Soft Earloop	-	IIR		
20326	Com-Fit Super High Filtration Face Mask with Soft Earloop	1	II		
20328	Com-Fit Super High Filtration Face Mask with Soft Earloop and Eye Shield	1	II		
20336	Com-Fit Super High Filtration Tie-On Face Mask	1	II		
20340	Com-Fit Easy Breathe Face Mask, Soft Earloop	-	II		
20342	Com-Fit Easy Breathe Face Mask, Tie-On	-	II		
20344	Com-Fit Super Sensitive Tie-On Face Mask	1	II		
20346	Com-Fit Super Sensitive Face Mask with Soft Earloop	1	II		
20350	Com-Fit Groovy Face Mask with Soft Earloop	-	IIR		
20352	Com-Fit Plush Face Mask With Soft Earloop, ASTM Level 1	1	II		
20353	Com-Fit Plush Face Mask With Soft Earloop, ASTM Level 2	2	IIR		
20354	Com-Fit Plush Face Mask With Soft Earloop, ASTM Level 3	3	IIR		
20355	Com-Fit Plush Natural Fit Face Mask with Soft Earloop, ASTM 1	1	II		
20356	Com-Fit Plush Natural Fit Face Mask with Soft Earloop, ASTM 2	2	IIR		
20357	Com-Fit Plush Natural Fit Face Mask with Soft Earloop, ASTM 3	3	IIR		

Table 2 summarizes the performance requirements that must be met for each ASTM F2100 Level.

Table 2: Medical Face Mask Material Requirements by Performance Level (ASTM F2100-19)					
Characteristic		Level 2	Level 3		
Bacterial filtration efficiency, %	<u>></u> 95	<u>></u> 98	<u>></u> 98		
Differential pressure, mm H ₂ O/cm ²	< 5.0	< 6.0	< 6.0		
Sub-micron particulate filtration efficiency at 0.1 micron, %	<u>></u> 95	<u>></u> 98	<u>></u> 98		
Resistance to penetration by synthetic blood, minimum pressure in mmHg for pass result	80	120	160		
Flame Spread	Class 1	Class 1	Class 1		

Table 3 summarizes the performance requirements that must be met for each EN 14683 Type.

Table 3: Performance Requirements for Medical Face Masks (EN 14683:2019)					
Test	Type I ^a	Type II	Type IIR		
Bacterial filtration efficiency, %	<u>≥</u> 95	<u>></u> 98	<u>></u> 98		
Differential pressure, Pa/cm²	< 40	< 40	< 60		
Splash resistance pressure, kPa	Not re	Not required			
Microbial Cleanliness, cfu/g	≤ 30	<u><</u> 30	<u><</u> 30		

^a Type I medical face masks should only be used for patients and other persons to reduce the risk of spread of infections particularly in epidemic or pandemic situations. Type I masks are not intended for use by healthcare professionals in an operating room or in other medical settings with similar requirements.